



Cross
Hire
Services

TTR 500 D Desiccant Dehumidifier

2.2 Kg/Hr Removal Capacity

www.crosshireservices.ie



Heating & Cooling

- 2 fans with separate air flow routing
- Air flow rate – continuously regulatable
- Quick and easy filter replacement
- Extremely easy maintenance and service-friendly construction
- Suitable for installation in false ceilings
- Housing made of sheet steel, galvanized and powder coated
- Can be stacked to save space
- Lightweight and easy-to-handle
- Quality premium components
- Practice optimized German industrial design – protected design
- Hygrostat connection
- Durable, robust and reliably

Specification Overview	
Operating range	0 to 100% r.H. / -15 °C to +35 °C
Dehumidification performance	ca. 2,2 kg/h
Air flow rate	180 - 550m ³ /h
Nominal air volume/ext. pressure	480m ³ /h / 150 Pa
Regeneration air/ext. pressure	80m ³ /h / 80 Pa
Dry air connection	ø 125 mm
Moist air connection	ø 80 mm
Electrical connection	230V - 50/60 Hz – ca. 3.0 kW
Dimensions	ca. 450 x 400 x 455 mm
Weight	ca. 25 kg

We are happy to provide further information



1890 247 266

DUBLIN +353 01 4048770
CORK +353 021 4930870
NI +44 078 92728580



info@crosshireservices.ie



www.crosshireservices.ie