

Specification Date Sheet | Model: 200TTIMDG



TRANSTANK CONTAINER 20500 Litre

TransTank Container, 110% bunded (double wall), ISO fuel tank container, ADR, ch.6.7, CSC, IMDG (IMO), RID, UIC, UN, USDot, TIR Approved for transport and UL142 and ULC-S601 for storage of diesel fuel.

- ❖ CSC plated ISO container (Convention for Safe Container Standard).
- ❖ Internal baffles to prevent fuel surge and provide safe handling and transportation at any fill level.
- ❖ Corner twist locks top and bottom and forklift pockets for ease of handling (forklift empty only).
- ❖ Standard 20' ISO container frame specifications for economical logistics.
- ❖ Can be stacked 6 high full of fuel, reducing transport and storage space requirements.
- ❖ Pressed heavy steel exterior plates for additional strength.
- ❖ Inner tank assembly approved to ADR ch.6.7 standard for transport. Tank material approved for use down to -40°C.
- ❖ Fast fill fuel pipe and high quality tank contents gauge.
- ❖ Option for 4 sets of feed & return connections, plus pump/auxiliary equipment feed. For additional security, hoses can be fed through access holes enabling doors to be kept locked while in use.
- ❖ Inner tank enclosed in steel weatherproof bund, with 110% capacity, for the storage of fuel in accordance with PPG2 Regulations.
- ❖ Pump & tank fittings all housed in lockable, vented cabinet within the bunded area and are top mounted to help prevent leakage.
- ❖ Unique fold down cabinet step for ease of access to tank fittings and pump.
- ❖ Exterior finish in high quality gloss paint, using a 2-pack epoxy system (Customer colours optional).

SPECIFICATION

Standard Tank Fittings: 2" Fill : 2" Vent Pipe with Valve : Pressure Vacuum Vent : 8 x 1½" Ports for Feed & Return Lines : Gauge : 2" Fitting for extra draw-off (optional) : Bolted Inspection Manhole : 4 x 3" Fusible Caps: 2 x Letterbox for Hose Feed			
Capacity Litres:	20500 (with overfill protection)	Inner Tank Thickness:	6mm (minimum)
Capacity (IMP) Gallons:	4509	Bund Material:	3mm (nominal)
Dimensions (mm):	L6058 x W2438 x H2438	Design Approvals:	As specified above
Weight ¹ Empty (Approx Kg):	6500	Design Standards:	ADR, ch.6.7, 49CFR, UL142,
Weight ¹ Full (Approx Kg):	22800		COP Regulations (PPG2)

Notes

¹ Laden weight of container is based on diesel weight of 0.84 kg/litre

Revision Date: 18/06/2015

